




**Fig 9: Angle Knee Bracket**



**Material:** Steel  
**Service Application:** Recommended for use on the sides of steel, concrete or wooden beams.  
**Finish:** Black, galvanized or painted.  
**Ordering:** Specify Size, figure number and finish.

| SIZE NO. | HOLE SIZE A     | B              | C              | D                | E              | WGT./C APPROX. | MAX. REC. LOAD, LB. |
|----------|-----------------|----------------|----------------|------------------|----------------|----------------|---------------------|
| 1        | $\frac{7}{16}$  | 2              | $\frac{3}{16}$ | $1\frac{1}{8}$   | 2              | 41             | 305                 |
| 2        | $\frac{9}{16}$  | 2              | $\frac{1}{4}$  | $1\frac{1}{8}$   | 2              | 53             | 565                 |
| 3        | $1\frac{1}{16}$ | 2              | $\frac{1}{4}$  | $1\frac{1}{8}$   | 2              | 53             | 905                 |
| 4        | $1\frac{1}{16}$ | $2\frac{1}{2}$ | $\frac{1}{4}$  | $1\frac{3}{8}$   | $2\frac{1}{2}$ | 85             | 905                 |
| 5        | $1\frac{1}{16}$ | 3              | $\frac{1}{4}$  | $1\frac{5}{8}$   | 3              | 123            | 905                 |
| 6        | $1\frac{1}{16}$ | 4              | $\frac{1}{4}$  | $2\frac{1}{8}$   | 4              | 220            | 905                 |
| 7        | $1\frac{3}{16}$ | 3              | $\frac{3}{8}$  | $1\frac{11}{16}$ | 3              | 180            | 1355                |
| 8        | $1\frac{3}{16}$ | 4              | $\frac{1}{4}$  | $2\frac{1}{8}$   | 4              | 220            | 1355                |
| 9        | $1\frac{5}{16}$ | 4              | $\frac{3}{8}$  | $2\frac{3}{16}$  | 4              | 327            | 1870                |
| 10       | $1\frac{1}{16}$ | 4              | $\frac{1}{2}$  | $2\frac{1}{4}$   | 4              | 427            | 2480                |