

Phone: (718) 507-8844 Fax: (718) 565-6018 Email: <u>info@irauch.com</u> Address: 32-20 112th St, East Elmhurst, NY 11369

Fig 333: Roller Support



The adjustment of the pipe line is had by turning the top nut which raises or lowers the pipe to desired pitch. The lower nut is then tightened locking support into position and prevents loosening due to vibration. To select the correct size Roller Support for use with Covered Piping and Pipe Covering Protection Saddles, refer to sizes shown in Fig 142 table.

Ordering:

Service

Application:

Order by size and figure number. Made special to customer order. Dimensions in inches.




FIG 333

PIPE	REC'M					STEEL	ROD	WT/C
SIZE	LOAD LB.	А	В	С	D	SIZE "E"	G	APROX
2	400	2 7/8	6	2 7/8	1 7/8	1/4 x 1 1/4	1/2	209
2 1/2		3 3/8		3 1/4	1 15/16			243
3		4		3 5/8	2			265
3 1/2		4 1/2		4	2 1/16			272
4	600	5 1/8	6	4 5/16	2 1/4	1/4 x 1 1/2	5/8	343
5	600	6 1/8	0	5 1/16	2 3/8	1/4 X 1 1/2	0/0	426
6	900	7 1/4	6	6	2 15/16	3/8 x 2	3/4	771
8	500	9 3/8	0	7 1/4	3 1/8	3/0 X Z	5/4	993
10	1100	11 1/2	6	8 13/16	3 9/16	1/2 x 2	1	1665
12	1100	13 1/2	0	10 5/16	3 7/8	1/2 X 2	1	1934

PROJECT INFOR	RMATION	APPROVED		
JOB:		NOTES:		
ADDRESS:				
CONTRACTOR:				
ENGINEER:				
DATE:				
APPROVED	NOT APPROVED	APPROVED AS NOTED		